



Standard Grade Blocks

Generated on 27.04.2020

Detailed description

Standard blocks are available in a range of thicknesses, which can be used above and below damp proof course (DPC) level.

Applications:

- Foundations.
- Internal and external leaf of cavity walls.
- Solid walls.
- Separating walls.
- Partitions.
- Multi-storey buildings.
- Beam and block floors; a separate BBA Certificate covers the product's use as floor infill.
- Flanking walls.

Product guidance - As Standard

Compressive strength:

3.6 N/mm².

Thermal conductivity:

0.15 W/m·K.

Density:

600 kg/m³.

Product specification

Manufacturer

- Name: H+H UK Ltd
- Web: www.hhcelcon.co.uk
- Email: info@hhcelcon.co.uk
- Tel: +44 (0)1732 886444
- Fax: +44 (0)1732 886810
- Address: Celcon House, Ightham, Borough Green, Kent TN15 9HZ

Product reference Celcon Standard Grade Blocks - Face size:
440 x 215 mm.

H+H UK Ltd



H+H UK Ltd
Celcon House
Ightham
Borough Green
Kent
TN15 9HZ

Tel: +44 (0)1732 886444

www.hhcelcon.co.uk
info@hhcelcon.co.uk



Celcon Standard Grade Plus Blocks - Face size: 630 x 215 mm.

Celcon Standard Grade Jumbo Blocks - Face size: 630 x 250 mm.

Thickness

75 mm - For Celcon Solar and Standard Grade Blocks only.

100 mm

140 mm

150 mm

215 mm