

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**EVO-STIK MULTI-PURPOSE SILICONE SEALANT WHITE** 

Revision date 24-Jan-2022 Supercedes Date: 12-Mar-2021 **Revision Number** 2

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

**Product Name EVO-STIK MULTI-PURPOSE SILICONE SEALANT WHITE** 

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant. Uses advised against None known

#### 1.3. Details of the supplier of the safety data sheet

**Company Name Bostik Limited** Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

**United Kingdom** +44 (1785) 272650

Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Chronic aquatic toxicity Category 3 - (H412)

## 2.2. Label elements

## Signal word

None

#### **Hazard statements**

H412 - Harmful to aquatic life with long lasting effects.

#### **EU Specific Hazard Statements**

EUH208 - Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] & Dimethylbis[(1-oxoneodecyl)oxy]stannane. May produce an allergic reaction

#### Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P273 - Avoid release to the environment

P501 - Dispose of contents/ container to an approved waste disposal plant

#### 2.3. Other hazards

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

#### PBT & vPvB

United Kingdom - BE Page 1 / 13

Revision date 24-Jan-2022

**Revision Number** 2

**EVO-STIK MULTI-PURPOSE SILICONE SEALANT WHITE** 

Supercedes Date: 12-Mar-2021

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Not applicable

#### 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	934-956-3	RR-100252-4	>25 - <40	Asp. Tox. 1 (H304)		01-2119827000- 58-XXXX
Triacetoxy(propyl)silane	241-816-9	17865-07-5	1 - <3	Skin Corr. 1B (H314) (EUH071)		01-2119966899- 07-XXXX
Silanetriol, methyl-, triacetate	224-221-9	4253-34-3	1- <2.5	Skin Corr. 1C (H314) Acute Tox. 4 (H302) (EUH014)		01-2119962266- 32-XXXX
Titanium dioxide	236-675-5	13463-67-7	0.1 - <1	Carc. 2 (H351i)		01-2119489379- 17-XXXX
4,5-dichloro-2-octyl-2H-i sothiazol-3-one [DCOIT]	264-843-8	64359-81-5	0.01 - <0.05	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) M=100 Aquatic Chronic 1 (H410) M=100 (EUH071)	Skin Irrit. 2 :: 0.025%<=C<5% Eye Irrit. 2 :: 0.025%<=C<3% Skin Sens. 1A :: C>=0.0015%	-
Dimethylbis[(1-oxoneode cyl)oxy]stannane	273-028-6	68928-76-7	0.01 - <0.05	Skin Irrit. 2 (H315) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Aquatic Chronic 3 (H412)		01-2120770324- 57-xxxx

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

United Kingdom - BE Page 2/13

#### **EVO-STIK MULTI-PURPOSE SILICONE SEALANT WHITE**

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### **SECTION 4: First aid measures**

Supercedes Date: 12-Mar-2021

#### 4.1. Description of first aid measures

**General advice** Show this safety data sheet to the doctor in attendance. If medical advice is needed,

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Immediately flush with plenty of water. After initial flushing, remove any contact lenses Eye contact

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Ingestion If swallowed, rinse mouth with water (only if the person is conscious). Never give

anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink

Revision date 24-Jan-2022

**Revision Number** 2

1 or 2 glasses of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

#### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

chemical

**Specific hazards arising from the** Thermal decomposition can lead to release of irritating gases and vapours.

Carbon dioxide (CO2). Silicon oxides. Silicon dioxide. Thermal decomposition can lead **Hazardous combustion products** 

to release of irritating and toxic gases and vapours.

5.3. Advice for firefighters

precautions for fire-fighters

**Special protective equipment and** Wear self contained breathing apparatus for fire fighting if necessary.

#### SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Do not get in eyes, on skin, or on clothing. Use personal protective equipment as Personal precautions

required. Ensure adequate ventilation.

United Kingdom - BE Page 3 / 13

**EVO-STIK MULTI-PURPOSE SILICONE SEALANT WHITE** 

Revision date 24-Jan-2022

**Revision Number** 2

6.2. Environmental precautions

Supercedes Date: 12-Mar-2021

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after

work. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from moisture. Keep away from food, drink and animal feedingstuffs.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

**Exposure Limits** Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon

curing This product contains titanium dioxide in a non-respirable form. Inhalation of

titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Acetic acid	TWA: 25 mg/m <sup>3</sup>	TWA: 10 ppm
64-19-7	TWA: 10 ppm	TWA: 25 mg/m <sup>3</sup>
	STEL: 50 mg/m <sup>3</sup>	STEL: 20 ppm
	STEL: 20 ppm	STEL: 50 mg/m <sup>3</sup>
Titanium dioxide	-	TWA: 10 mg/m <sup>3</sup>
13463-67-7		TWA: 4 mg/m <sup>3</sup>
		STEL: 30 mg/m <sup>3</sup>
		STEL: 12 mg/m <sup>3</sup>

United Kingdom - BE Page 4 / 13

**EVO-STIK MULTI-PURPOSE SILICONE SEALANT WHITE** 

Supercedes Date: 12-Mar-2021 Revision Number 2

Revision date 24-Jan-2022

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)							
Titanium dioxide (13463-67-7)							
Type	Exposure route	Derived No Effect Level	Safety factor				
	•	(DNEL)	•				
worker	Inhalation	10 mg/m <sup>3</sup>					
Long term							
Local health effects							

Derived No Effect Level (DNEL)							
Titanium dioxide (13463-67-7)	Titanium dioxide (13463-67-7)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor				
Consumer Long term	Oral	700 mg/kg bw/d					
Systemic health effects							

**Predicted No Effect Concentration** No information available. **(PNEC)** 

Predicted No Effect Concentration (PNEC)				
Titanium dioxide (13463-67-7)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Marine water	0.0184 mg/l			
Freshwater sediment	1000 mg/kg			
Freshwater	0.184 mg/l			
Marine sediment	100 mg/kg			
Soil	100 mg/kg			
Microorganisms in sewage treatment	100 mg/l			
Freshwater - intermittent	0.193 mg/l			

#### 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

gloves. Gloves must conform to standard EN 374

Skin and body protection Respiratory protection

None under normal use conditions.

In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

**Recommended filter type:** Organic gases and vapours filter conforming to EN 14387. White. Brown.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Physical state Solid

United Kingdom - BE Page 5 / 13

**EVO-STIK MULTI-PURPOSE SILICONE SEALANT WHITE** 

Revision date 24-Jan-2022

**Revision Number** 2

\_\_

Appearance Paste
Colour White
Odour Acetic acid

Supercedes Date: 12-Mar-2021

Odour threshold No information available

Property Values Remarks • Method

**pH** No data available Not applicable Insoluble in water

pH (as aqueous solution)

Melting point / freezing point

Initial boiling point and boiling

No data available
No data available

range

Flash point > 100 °C CC (closed cup)

**Evaporation rate** No data available **Flammability** No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressure No data available Relative vapour density No data available

Relative density 0.97

Water solubility Product cures with moisture

Solubility(ies)

Partition coefficient

Autoignition temperature

Decomposition temperature

No data available

Kinematic viscosity > 21 mm²/s @ 40 °C

Dynamic viscosity

Explosive properties

Oxidising properties

No data available

No data available

No data available

9.2. Other information

Solid content (%) No information available

**VOC Content (%)** 

**Liquid Density** 0.97 g/cm<sup>3</sup>

## **SECTION 10: Stability and reactivity**

10.1. Reactivity

**Reactivity** Product cures with moisture.

10.2. Chemical stability

**Stability** Stable under normal conditions.

**Explosion data** 

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over

United Kingdom - BE Page 6 / 13

**EVO-STIK MULTI-PURPOSE SILICONE SEALANT WHITE** 

·

prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and

Revision date 24-Jan-2022

**Revision Number** 2

sources of ignition.

10.5. Incompatible materials

Supercedes Date: 12-Mar-2021

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

**Hazardous decomposition** 

products

None under normal use conditions. Stable under recommended storage conditions.

## SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

#### Information on likely routes of exposure

Product Information

**Inhalation** Based on available data, the classification criteria are not met.

**Eye contact** Based on available data, the classification criteria are not met.

**Skin contact** Based on available data, the classification criteria are not met. May cause sensitisation

in susceptible persons.

**Ingestion** Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

Numerical measures of toxicity

#### **Acute toxicity**

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	LD50 > 5000 mg/kg (Rattus) OECD 401	LD50 > 3160 mg/kg (Oryctolagus cuniculus) OECD 402	LC50 Inhalation(4h) >5266 MG/M3 (Rattus)
Silanetriol, methyl-, triacetate 4253-34-3	LD50 = 1600 mg/kg (Rattus) OECD 401		
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 10000 mg/Kg	>5 mg/l
4,5-dichloro-2-octyl-2H-isothiaz ol-3-one [DCOIT] 64359-81-5	=1636 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	=0.26 mg/L (Rattus) 4 h
Dimethylbis[(1-oxoneodecyl)ox y]stannane 68928-76-7	LD50 =892 mg/Kg (Rattus) (OECD 401)	LD50 >2000 mg/Kg (rattus)	

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation**The assessment of the result of testing was done in accordance with the guideline of the

United Kingdom - BE Page 7 / 13

#### **EVO-STIK MULTI-PURPOSE SILICONE SEALANT WHITE**

Supercedes Date: 12-Mar-2021

Revision date 24-Jan-2022 **Revision Number** 2

Commission 92/69/EEC.

Product Information							
Method	Species	Exposure route	Effective dose	Exposure time	Results		
	Rabbit	Dermal		6 days	Product score <=1		
					Non-irritant		

Serious eye damage/eye irritation By analogy to another tested similar product: No irritation after contact to the eyes. (H319 is void). The assessment of the result of testing was done in accordance with the guideline of the Commission 92/69/EEC.

Product Information							
Method	Species	Exposure route	Effective dose	Exposure time	Results		
	Rabbit	eye		6 days	Product score		
					<=1		
					Non-irritant		

Respiratory or skin sensitisation

No classification is proposed, based on conclusive negative data. May produce an allergic reaction. OECD Test No. 406: Skin Sensitisation. May cause sensitisation in susceptible persons.

Product Information						
Method	Species	Exposure route	Results			
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses			
Sensitisation			were observed			

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Chemical name	European Union
Titanium dioxide	Carc. 2
13463-67-7	

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Based on available data, the classification criteria are not met. Reproductive toxicity

Based on available data, the classification criteria are not met. STOT - single exposure

STOT - repeated exposure Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

11.2.2. Other information

No information available. Other adverse effects

United Kingdom - BE Page 8 / 13

Revision date 24-Jan-2022

**EVO-STIK MULTI-PURPOSE SILICONE SEALANT WHITE** 

Supercedes Date: 12-Mar-2021 Revision Number 2

## **SECTION 12: Ecological information**

#### **12.1. Toxicity**

**Ecotoxicity** 

Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	EL50 (72h) >10,000 mg/L (Skeletonema costatum) ISO 10253	LL50 (96h) > 1028 mg/L (Scophthalmus maximus) OECD 203	-	LL50 (48h)> 3193 mg/l (Acartia tonsa)		
Triacetoxy(propyl)silan e 17865-07-5	EC50 (72h): approx. 24 mg/l(Pseudokirc henriella subpicata)	LC50 (96h) = 108.89 mg/L	-	EC50 (48h) = 89.59 mg/L		
Silanetriol, methyl-, triacetate 4253-34-3	EC50 (72h): >500 mg/l (Pseudokirchner ella subcapitata)	LC50 (96h) >500 mg/l (Brachydanio rerio)	-	EC50 (48h) >500 mg/l (Daphnia magna)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
4,5-dichloro-2-octyl-2H- isothiazol-3-one [DCOIT] 64359-81-5	EC50 (72h) =0.025 mg/L Algae (Scenedesmus subspicatus)(OE CD 201)	LC50 (96h) 0.0078 mg/L (Oncorhynchus mykiss)(OECD 203)	-	EC50 (48h) 0.0097 mg/L Daphnia magna (OECD 202)	100	100
Dimethylbis[(1-oxoneod ecyl)oxy]stannane 68928-76-7	-	-	-	EC50 =39 mg/L (Daphnia magna) (OECD 201)		

## 12.2. Persistence and degradability

Persistence and degradability Not readily biodegradable.

Component Information						
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)						
Method	Exposure time	Value	Results			
OECD Test No. 308: Aerobic and		Half-life	1.1-1.3 days			
Anaerobic Transformation in			-			
Aquatic Sediment Systems						

Dimethylbis[(1-oxoneodecyl)oxy]stannane (68928-76-7)				
Method	Exposure time	Value	Results	
OECD Test No. 301B: Ready	28 days	0%	Not readily biodegradable	
Biodegradability: CO2 Evolution				
Test (TG 301 B)				
OECD Test No. 301F: Ready	28 days	3%	Not readily biodegradable	
Biodegradability: Manometric	-			
Respirometry Test (TG 301 F)				

United Kingdom - BE Page 9 / 13

**EVO-STIK MULTI-PURPOSE SILICONE SEALANT WHITE** 

Supercedes Date: 12-Mar-2021 Revision Number 2

Revision date 24-Jan-2022

\_\_\_

12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

#### **Component Information**

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Triacetoxy(propyl)silane	1.23	-
17865-07-5		
Silanetriol, methyl-, triacetate	-2.4	-
4253-34-3		
4,5-dichloro-2-octyl-2H-isothiazol-3-one	4.4	13
[DCOIT]		
64359-81-5		

#### 12.4. Mobility in soil

Mobility in soil No information available.

#### 12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB.

01	557 1 5 5
Chemical name	PBT and vPvB assessment
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03%	The substance is not PBT / vPvB
aromatics	
RR-100252-4	
Triacetoxy(propyl)silane	The substance is not PBT / vPvB
17865-07-5	
Silanetriol, methyl-, triacetate	The substance is not PBT / vPvB
4253-34-3	
Titanium dioxide	The substance is not PBT / vPvB
13463-67-7	PBT assessment does not apply
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	The substance is not PBT / vPvB
64359-81-5	

#### 12.6. Other adverse effects

Other adverse effects No information available.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste from residues/unused products

Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international

regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

**European Waste Catalogue** 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

## **SECTION 14: Transport information**

United Kingdom - BE Page 10 / 13

#### **EVO-STIK MULTI-PURPOSE SILICONE SEALANT WHITE**

Revision date 24-Jan-2022

**Revision Number** 2

#### Land transport (ADR/RID)

Supercedes Date: 12-Mar-2021

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

#### **IMDG**

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Marine pollutantNP

14.5 Marine pollutant NP
14.6 Special Provisions None

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

#### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

## Section 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **European Union**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

## **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

United Kingdom - BE Page 11 / 13

#### **EVO-STIK MULTI-PURPOSE SILICONE SEALANT WHITE**

Supercedes Date: 12-Mar-2021

Revision date 24-Jan-2022 Revision Number 2

### **Persistent Organic Pollutants**

Not applicable

#### National regulations

#### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

#### **SECTION 16: Other information**

#### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

EUH014 - Reacts violently with water

EUH071 - Corrosive to the respiratory tract

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H351i - Suspected of causing cancer if inhaled

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H412 - Harmful to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
\* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

## Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 24-Jan-2022

Indication of changes

**Revision note** SDS sections updated: 2, 3, 11, 13, 15, 16.

United Kingdom - BE Page 12 / 13

Revision date 24-Jan-2022 Revision Number 2

**EVO-STIK MULTI-PURPOSE SILICONE SEALANT WHITE** 

Supercedes Date: 12-Mar-2021

\_\_\_\_\_

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

United Kingdom - BE Page 13 / 13