



Never compromise on quality!



EXTERIOR PREGRIT

Extra Grip Render Bonding Agent



BUILDERS COMPLETE RANGE

Description:

A one part, ready-to-use, extra grip, external render bonding agent with added aggregate to provide a key prior to applying render to exterior substrates.

Benefits:

- ◆ Bonding agent for exterior walls.
- ◆ For use on concrete, brickwork, light blockwork.
- ◆ Single application, render once cured.
- ◆ Light green in colour for easy identification of treated areas.
- ◆ Reduces suction on porous surfaces.
- ◆ Improves adhesion on smooth surfaces.
- ◆ Waterproof.

Uses

EXTERIOR PREGRIT is for use as an effective bonding agent for render to concrete, brickwork and blockwork. And as a bonding agent to improve adhesion to smooth surfaces.

Application

Thoroughly stir before use. Ensure application temperature is above +5°C and that the surface to be treated is free from dust, release agents and any contaminants that may hinder adhesion. Any contamination must be removed prior to application, including any flaking material. Ensure the background is sound and will support the weight of the render. Do not dilute. We recommend a patch test be carried out on a small inconspicuous area to test compatibility prior to full application. Simply apply 1 coat using a brush or roller ensuring an even coat and allow to dry (6 hours minimum). This product is coloured light green to identify treated areas. Protect adjacent surfaces from splashes and remove any EXTERIOR PREGRIT before drying using warm soapy water.

Note: Cold or humid conditions will increase drying times. Do not use at temperatures below +5°C.

Limitations

- Do not use on areas subject to continual damp.
- Do not dilute.
- Do not exceed a maximum thickness of 25mm for complete render system.
- Remove any contamination of product to surrounding surfaces before drying.

Coverage

10L of EXTERIOR PREGRIT will cover approximately 30m² depending on porosity of substrate.

Container Size

10L recycled plastic tub.

Colour

Pale green in colour.

Shelf Life

24 months from date of manufacture when stored in sealed tubs.

Storage Conditions

Store in cool, dry conditions in the original sealed container away from direct sunlight. Store between +5°C and +30°C and protect from frost.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations. Any spillages should be mopped up immediately with an inert absorbent material such as sand or sawdust.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Specific Gravity	1.25g/ml
Viscosity	6,000 - 12,000 cP
Appearance	Pale green liquid
Tub PCR Content	30%

Product Details:

Colour:	Pale Green
Code:	BDEPG10
Size:	10L
Barcode:	5060021369710



Part of the Bond It Builders Complete Range

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001



BOND IT
 Head Office: Unit G16 River Bank Way, Lowfields Business Park,
 Elland, West Yorkshire HX5 9DN.
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V1 06/02/14
 Reviewed: 07/4/22